

PARKETOLIT

1C MS (modified silane) adhesive for parquet

E65

EASY-TO-USE & FAST GLUING OF PARQUET

Easy-to-use

PARKETOLIT E65 is one-component adhesive ready to use. Adhesive is tixotropic, keeps the form of applying and can be easily spread.

Fast

Adhesive hardens with humidity cross-linking reaction. Full traffic and additional working operations: sanding and lacquering are possible after 24 hours.

Economic

Due to excellent characteristics is the consumption of adhesive 20% lower comparing to two comp. adhesives. Additional saving is achieved by innovative packaging into Al foil enabling maximal utilization of the glue.

Excellent adhesion

Excellent adhesion of Parketolit E65 allows gluing of all types of parquet on any kind of surface, even without using primer.

Permanently elastic adhesive

Allows natural adaptation of wooden floor to ambient conditions and improves sound isolation of the floor.

Easy-to-clean

PARKETOLIT E65 is highly recommended for laying prefinished parquet because of easy cleaning of adhesive residues from parquet surface. Allows also easy removing from tools and hands.

User friendly

PARKETOLIT E65 is distinguished by neutral odour and very low emission. It is a hazard-symbols free.

According to EN 14293:2006 and ISO 17178:2013 for elastic adhesives requests.

For more information please call on telephone **+ 386 573 12 315** or mail to prodaja@mitol.si.



**User friendly,
Permanently elastic adhesive**



**Universal use,
Easy-to-clean**



MITOL, tovarna lepil, d.o.o., Sežana, Partizanska c. 78, 6210 Sežana, Slovenija
T: +386 5 73 12 300, F: +386 5 73 12 390, E: mitol@mitol.si, I: www.mitol.si

CHOOSE THE RIGHT ADHESIVE

	PARKETOLIT 1513	PARKETOLIT 1514	PARKETOLIT 1549	PARKETOLIT 1550	PARKETOLIT 1551	PARKETOLIT 1554	PARKETOLIT 1555	PARKETOLIT E60	PARKETOLIT E61	PARKETOLIT E65	PARKETOLIT E66	PARKETOLIT D3	MEKOL 1560	MEKOL 1570	MEKOL 1580	MITOPUR 1530
SOLID PARQUET ELEMENTS																
• on concrete or on leveller	■	■	●	●	●	●	●	●	●	●	●					
• on wooden floors		■	●	●	●	●	●	●	●	●	●					
• on nonporous surfaces			●	●	●	●	●	●	●	●	●					
• on heated floors			●	●	●	■	■	●	●	●	●					
• on concrete with increasing moisture			■	■	■	■	■	●	●	■	■					
• unstable wood (beech, ash...)			■	■	■	■	●	●	●	●	●					
MOSAIC PARQUET																
• on concrete or on leveller	●	●	●	●	●	●	●	●	●	●	●					
• on wooden floors		●	●	●	●	●	●	●	●	●	●					
• on nonporous surfaces			●	●	●	●	●	●	●	●	●					
• on heated floors	●	■	●	●	●	■	■	●	●	●	●					
• on concrete with increasing moisture			■	■	■	■	■	●	●	■	■					
• unstable wood (beech, ash...)			●	●	●	●	●	●	●	●	●					
SOLID LAMPARQUET			●	●	●	●	●	●	●	■	■					
SOLID BOARDS			●	●	●	●	●	■	■	■	■					
MULTY-LAYER PARQUET			■	■	■	●	●	●	●	●	●	●				
SOLID VERTICAL FINGER PARQUET			●	●	●	●	●	●	●	●	●					
LAMINATED FLOORS								■	■	■	■	●				
PVC													●	●	●	■
TEXTILE COVERINGS													●	●		
CORK (natural, plastic)														●		
RUBBER			■	■	■			■	■	■	■				●	●
LINOLEUM															●	
CERAMIC TILES			■	■	■	■	■	■	■	■	■					■
ARTIFICIAL GRASS			■	■	■	■	■									●
WOODEN STEPS			■	■	■	■	■	■	■	■	■					■

● basic use

■ possible use

